

LENNO

TECHNICAL DESCRIPTION

FRAME

Solid wood and plywood.

SUSPENSION

Interwoven elastic webbing.

STRUCTURE PADDING

High resilience polyurethane cold-molded foam 75/SR, 40/TL, T30/C and polyester fibre 200 gr/m² coupled with a polyester fabric.
 75 kg/m³ = 14,0 kPa of bearing capacity* at 40% compression.
 40 kg/m³ = 6,6 kPa of bearing capacity* at 40% compression.
 30 kg/m³ = 2,7 kPa of bearing capacity* at 40% compression.

SEAT CUSHION PADDING

High resilience polyurethane cold-molded foam 40/PH, 32/EM
 40 kg/m³ = 8,0 kPa of bearing capacity* at 40% compression.
 32 kg/m³ = 3,8 kPa of bearing capacity* at 40% compression.
 The cushion is then wrapped in a special, anti-perforation 100% cotton quilted lining of Piumafill (50% feathers, 50% polyester fibres).
 All padding is wrapped in polyester fabric = 100 gr/m².
 Removable cover by zipper.
 Loose cushion.

BACK PADDING

Piumafill (50% feathers, 50% polyester fibres) wrapped in a special, anti-perforation 100% cotton cover.
 Removable cover by zipper.
 Loose cushion.

THIN ARM CUSHION FILLING

Polyester fibre DACRON DU PONT 808/T 650 gr/m².

REMOVABLE HEAD REST

Matt black lacquer steel.
 Piumafill (50% feathers, 50% polyester fibres) wrapped in a special, anti-perforation 100% cotton cover.
 Removable cover when fabric.

FEET

Matt black lacquer steel.
 Central foot for sizes 210 and 230.

BED-SOFA

Not available.

REMOVABLE COVER

When in fabric, cover is entirely removable by fastening strip;
 when in leather, cover is not removable.

OPTIONAL CUSHIONS

Piumafill (50% feathers, 50% polyester fibres).

The presence of feathers or polyester fibres gives an intentionally soft appearance. This is incompatible with the tastes of customers loving rigid cushions. With the aim of improving quality, Triss reserves the right to make any technical and material change without notice.

